

# System monitoring with Nagios and SNMP

The server systems of m-privacy GmbH have sensors for NRPE-based monitoring systems (e.g. Nagios) or for SNMP-based monitoring systems. This allows important operating states to be checked remotely so that countermeasures can be taken before critical limit values are exceeded. The following list provides an overview of the implemented checks.

Not every system has the total number of possible sensors, so not all check points must always be active. The specified threshold values are predefined, but can be changed if necessary.

## Hint

In order for TightGate-Pro to be monitored with a monitoring system, the monitoring must be activated as administrator **config** under **Services > Nagios NRPE Support/Start SNMP Service**. In addition, the IP address of the monitoring server must be stored under **Services > Maintenance and Updates > Remote Administrator IP**.

## Caution

It must be ensured that the checks are not executed simultaneously, especially not in parallel on all nodes. An even distribution of the checks should be aimed for. Checks that are only carried out once a day anyway (every 1440 minutes) should preferably be carried out at night, whereby simultaneous execution should also be avoided here.

## Manual check of NRPE checkpoints

As **root** enter the following command in the console:

```
cd /usr/lib/nagios/plugins/
```

```
./check_nrpe -H [IP address of TightGate-Pro] -c check_[name of checkpoint]
```

Ex. for the checkpoint maint:

```
./check_nrpe -H 192.168.4.1 -c check_maint
```

## Manual check of SNMP checkpoints

Enter the following command from the monitoring computer to read out individual checks:

```
snmpget -v3 -u snmp-user -A [PASSWORD] -a SHA -l authnoPriv [IP address of TightGate-Pro] [single MIB or OID]
```

## Hinweis

Here you will find a [complete list of all MIBs and OIDs of the test points from TightGate-Pro.](#)

## Basic checkpoints

Checkpoint	Description	State OK	State Warning	State Critical	Activity at Warning	Activity at Critical	Check interval (in minutes)
maint	Checks whether a node is available and not in maintenance mode. If applicable, displays the time of a scheduled maintenance.	Node available and not in maintenance mode	Node in maintenance mode		Log in as administrator <b>maint</b> and exit maintenance mode after maintenance is complete.		30
load	Returns the average system load for the time points: 1, 5 and 15 minutes.	The workload is lower than the value set by the administrator config under the system preferences	The workload is higher than the value set by the administrator config under the system preferences but less than twice the value	The workload is higher than twice the value set by the administrator config under the system preferences	Log in as administrator <b>root</b> and open a console. The command <b>atop</b> displays the process overview, indicating the load per process. The list can be sorted by load value by entering <b>p</b> in the window. Processes that cause particularly high load can be terminated using <b>kill</b> . Restarting the system can also help. In any case, if the system load is excessive, inform the technical customer service of m-privacy GmbH .		5
softmode	Checks whether the node is in softmode, i.e. in a state not protected by RSBAC.	Softmode is not activated		Softmode is activated	Please deactivate softmode as user <b>Security</b> .		10
users	Checks for the maximum number of VNC connections (TightGate viewer) stored as <b>config</b> and outputs the current number of viewer and lock connections.	< Max VNC	Über Max VNC aber unter Max VNC +10	> Max VNC +10	If the limit values are exceeded, performance losses are to be expected.		30

Checkpoint	Description	State OK	State Warning	State Critical	Activity at Warning	Activity at Critical	Check interval (in minutes)
disks	Checks free memory on the hard disks.	> 20% free	Between 20% and 10% free	< 10% frei	Statusseite des entsprechenden Systems aufrufen und Massenspeicher auf Belegung überprüfen. Bei Platzmangel sollten insbesondere die Benutzerverzeichnisse in /home geprüft werden. Evtl. können z. B. alte Backups gelöscht werden. Weiterhin sollten die Logdateien in /var/log geprüft werden. Zu große Logdateien können gelöscht werden, um Platz auf dem Datenträger zu schaffen.		60
zombie_procs	Undermined zombie processes, can indicate errors.	No zombie processes	Under 10 zombie processes	Over 10 zombie processes	Zombie processes can occur occasionally and usually do not affect system operation. Frequent occurrence of zombie processes indicates errors in file handling. It is recommended to inform the technical customer service of m-privacy GmbH .		60
ntp	Prüft die Erreichbarkeit von NTP-Zeitservern und zeigt Abweichungen zur lokalen Systemzeit an.	Zeitdifferenz < 60 Sekunden	Zeitdifferenz zwischen 60 und 120 Sekunden	Nicht erreichbar oder Zeitdifferenz > 120 seconds	Especially in cluster systems, all nodes must have the same system time. If the time difference to the reference of the stored NTP server is > 1 minute, action is required! Please log in as administrator <b>config</b> and use the menu item <b>Check network</b> to verify the problem and adjust the time if necessary. If necessary, an alternative external NTP server should be configured to ensure proper system operation.		30
memavailable	Display the available memory in kByte.	over 1,000,000 (1 GB RAM)	Value between 1,000,000 and 100,000	Value under 100,000 (100 MB RAM)	Increase the memory or reduce the number of users on the server.		5
memorypressurekilled	Number of user sessions that were automatically logged off due to acute memory shortage within the last 24 hours.	0	Value less than 0		Increase in memory or decrease in the number of users on the server.		1440
pressure_cpu	Checks whether requests are delayed due to a bottleneck in the CPU.	Delays <20% aller Anfragen	Verzögerungen zwischen 20%>50% of all requests	Delays >50% of all requests	The number of authorised users should be reduced on the node.		5

Checkpoint	Description	State <b>OK</b>	State <b>Warning</b>	State <b>Critical</b>	Activity at <b>Warning</b>	Activity at <b>Critical</b>	Check interval (in minutes)
pressure_io	Checks whether requests are delayed due to a read/write bottleneck or network bottlenecks.	Delays <20% aller Anfragen	Verzögerungen zwischen 20%>50% of all requests	Delays >50% of all requests		If SSDs are used, bottlenecks usually occur in connection with network bottlenecks.	5
pressure_memory	Checks whether requests are delayed due to a memory bottleneck.	Delays <2% aller Anfragen	Verzögerungen zwischen 2%>10% of all requests	Delays >10% of all requests		The available RAM should be extended or the number of authorised users on the node should be reduced.	5
ssh	Checks the reachability of a Secure Shell and returns the SSH version.	Reachable		Not reachable		If SSH is reported as unreachable, the administrator <b>config</b> should first execute a <b>Apply</b> . If SSH is still reported as unreachable, the system must be restarted in recover mode. In this case, it is recommended to contact the technical customer service of m-privacy GmbH .	5
dns	Checks the DNS server entered. Returns the IP address and the response time of the DNS server.	Resolution of the IP address possible.		Resolution of the IP address not possible.		Check DNS server, enter alternative DNS server if necessary.	5
bug	Searches the kern.log file for keywords that indicate kernel errors.	No errors found		Error found		Inform technical customer service of m-privacy GmbH .	1440
cron	Checks the number of running cron jobs.	1 to 10 cron jobs	Between 11 and 20 cron jobs	> 20 or no cron jobs		Log in as administrator <b>root</b> and call console. Command sequence <b>ps tree -ah</b> locates the blocked cron job. Check possible services and take appropriate action, e.g. as administrator <b>config Apply</b> or restart the system.	60

Checkpoint	Description	State OK	State Warning	State Critical	Activity at Warning	Activity at Critical	Check interval (in minutes)
versions	Compares the installed software version with the currently available software version. <b>Note:</b> This check can only be called up <b>directly a maximum of 2 times a day</b> . Each additional call returns the last result with the note " <b>(cached)</b> ". If you want to force the call, you can call up "Available updates" once beforehand ( <b>update</b> do not forget to log off again). The check is then run again.	No newer version available	Updates available	Updates available for more than 6 months	Log in as administrator <b>update</b> and <b>Perform autoupdate</b>		1440
vnc	Checks the accessibility of the VNC server and returns its response time and the port set.	Reachable		Not reachable	If VNC is activated in the configuration and is still reported as unreachable, the administrator <b>config</b> should first execute a <b>Full Apply</b> . If VNC is still shown as unreachable, the system must be restarted in recover mode. In this case, it is advisable to consult the technical customer service of m-privacy GmbH .		5
diskerror	Searches the kern.log file for keywords that indicate hard disk errors.	No errors found		Errors found	Warnings indicate faulty hard disks. This can lead to data inconsistencies or data loss. Please contact technical support at m-privacy GmbH .		1440
licence	Checks for a valid licence and returns the number of licences used and the expiry date.	Licence valid		Licence invalid	The licence must be renewed via the technical customer service of m-privacy GmbH .		1440
apply	Checks whether it is necessary to apply as Administrator Config.	No apply necessary		Apply necessary	If Nagios signals that an apply is necessary, please log in as administrator <b>config</b> and execute an <b>apply</b> .		10
slabs	Check for memory areas in the core.	< 10 Mio.	Zwischen 10 und 100 Mio.	> 100 million	Indicates memory leaks and core errors.		60

Checkpoint	Description	State OK	State Warning	State Critical	Activity at Warning	Activity at Critical	Check interval (in minutes)
backup	Checks for existing backup and any errors that may have occurred. Returns date and time of the last backup created, if found.	Backup exists and is free of errors	Backup is faulty or no automatic backup has been configured	Backup does not exist or service is not available	As administrator <b>backuser</b> Log in and check log for errors. It can be called up with the command <b>Show last log</b> .	Check whether as administrator <b>backuser</b> under <b>Configuration &gt; Frequency</b> inappropriate settings may have been selected. Then, for example, check in the log whether a backup was created and check for errors if necessary.	1440
smart_sd*	Checks the SMART status of the respective hard disk and returns the detected status. Replace the * character with the respective purchase plant letter.	Hard disk OK + current temperature	Temperature > 45 °C	Temperature > 50 °C		If the temperature is too high, the cooling of the system should be checked. If the hard disk is not OK, the errors of the S.M.A.R.T. check of the disk are also output. Measures can be a system start from the rescue system or execution of a <b>fsck</b> .	1440
definedusers	Checks the number of created users in TightGate-Pro and shows how many user IDs are currently created in TightGate-Pro.	At least 5 new user IDs can still be created.	Only a maximum of 5 new users can be created.	A maximum of one new identifier can still be created or the maximum number of user identifiers has already been reached.		Please purchase additional licences from TightGate-Pro.	1440

## Optional checkpoints

Optimal checkpoints can be used depending on the system configuration to monitor specific processes.

### Checkpoints for cluster system "Ceph

Depending on how many Ceph servers are in use, all Nagios checkpoints are provided for each Ceph server. The following table lists all checks for the first Ceph server. The checkpoints for the second and further Ceph servers are to be used in the same way, but the number given in the checkpoint is

to be incremented in each case.

Checkpoint	Description	State OK	Status Warning	State Critical	Activity at Warning	Activity at Critical	Check interval (in minutes)
homeusermount	Checks whether /home/user is mounted in the directory tree. Returns the path of /home/user.	Mounted		Not mounted	Check hard disk, if necessary mount user directories manually as a test. It could also be a file system error, so notifying technical support at m-privacy GmbH is recommended.		10
backupmount	Checks whether /home/backuser/backup has been correctly mounted in the directory tree.	Mounted		Not mounted	Check hard disk, if necessary mount user directories manually as a test. This could be a file system error, so notifying technical support at m-privacy GmbH is recommended.		60
check_ceph_hu_1_disks	Checks free memory on the hard disks of the first Ceph server.	> 20% free	Between 20% and 10% free	< 10 % frei	Ist der Speicher voll, nehmen Sie bitte Kontakt mit dem technischen Kundendienst der m-privacy GmbH auf.		60
check_ceph_hu_1_disk_load	Plattenaktivität aller verfügbaren Platten in %.	< 70%	Zwischen 70% und 90%	> 90%	Problematic with HDD.		60
check_ceph_hu_1_zombie_procs	Undermined zombie processes, can indicate errors.	No zombie processes	Under 10 zombie processes	Over 10 zombie processes	Zombie processes may occur occasionally and usually do not affect system operation. Frequent occurrence of zombie processes indicates errors in file handling. It is recommended to inform the technical customer service of m-privacy GmbH .		60
check_ceph_hu_1_ntp	Checks the accessibility of NTP time servers and displays deviations from the local system time.	Time difference < 60 Sekunden	Zeitdifferenz zwischen 60 und 120 Sekunden	Nicht erreichbar oder Zeitdifferenz > 120 seconds	In the event of deviations, it is essential to restore synchronicity, otherwise cluster failures may occur.		30

Checkpoint	Description	State OK	Status Warning	State Critical	Activity at Warning	Activity at Critical	Check interval (in minutes)
check_ceph_hu_1_ssh	Checks the accessibility of a Secure Shell and returns the SSH version.	Reachable		Not reachable		If SSH is reported as unreachable, the administrator <b>config</b> should first execute a <b>Apply</b> . If necessary, contact the technical customer service of m-privacy GmbH .	5
check_ceph_hu_1_cron	Checks the number of running cron jobs.	1 to 10 cron jobs running	11 to 20 cron jobs running	> 20 or no cron jobs running			60
check_ceph_hu_1_ceph	Displays the HEALTH status of the entire external Ceph.	Ceph is OK	Ceph has a problem	Ceph is not intact		Yes, depending on the problem, the error messages of the Ceph must be responded to individually. If necessary, contact the technical customer service of m-privacy GmbH .	10
check_ceph_hu_1_smart_sd*	Checks the SMART status of the respective hard disk and returns the detected status. The * sign is to be replaced by the respective purchase plant letter.	Hard disk OK + current temperature	temperature > 45 °C	temperature > 50 °C		If the hard disk is too hot, the fan settings or the air flow in the server must be checked.	1440

### Further optional checkpoints

Checkpoint	Description	Condition OK	State Warning	State Critical	Activity at Warning	Activity at Critical	Check interval (in minutes)
scanner	Checks whether the virus scanner's malware definitions are up-to-date and whether the virus scanner is running.	Definitions current (or not older than 2 days)	Definitions older than 2 days but younger than 1 week	Virus scanner is not running or no definitions are available or the definitions are older than 1 week.	Update virus definitions according to the administration manual.	Correctly configure as administrator <b>config</b> according to the administration manual.	1440
sensors	Check the hard disk temperature	Temperature below 110°C	Temperature above 110°C and below 120°C	Temperature above 120°C		There is a danger of overheating. Please check whether the fans are working properly. If necessary, make settings in the BIOS of the server. Please also check that the air flow around the server is guaranteed.	5



Checkpoint	Description	Condition OK	State Warning	State Critical	Activity at Warning	Activity at Critical	Check interval (in minutes)
squid	Checks the availability of the proxy server and displays the response time and the connection port.	All OK		Port not accessible Not accessible	If the port cannot be reached, check whether the service is running.		5
http	Checks for the availability of the HTTP protocol and outputs the response time.	All OK		Port Not reachable	If the port cannot be reached, check whether the service is running.		5
temp	Checks the temperature of the mainboard (if a sensor is present) and outputs it.	< 50 °C	50 °C to 60 °C	> 60 °C	If the temperature is exceeded, check the entire cooling system of the hardware (fan, heat sink, air ducts, etc.) and the air conditioning of the operating environment.		5
fan	Checks whether a fan is running (if sensor is present).	Running		Not running	Check hardware in case of problem message.		10
timedupdate	Checks whether an automatic update is scheduled.				The checkpoint only provides informative values for the planned update time.		1440
identd	Check identd- daemon for logging of proxy connections.	ok	No logging configured, but proxy is running	Logging is configured, but proxy is not running	Correct settings or restart service by <b>Apply</b> as <b>config</b> .		5
adldap	Check for accessibility of LDAP server / AD server during user administration				Indicates errors when using Active Directory or LDAP servers. Measures are to be taken according to the instructions of the check.		5
nodesavail	Checks for the availability of all nodes within a cluster of TightGate-Pro systems	All nodes are available	Fewer nodes are available than defined, but the minimum number is still present	No nodes are accessible/available.	Informative.		10

Checkpoint	Description	Condition <b>OK</b>	State <b>Warning</b>	State <b>Critical</b>	Activity at <b>Warning</b>	Activity at <b>Critical</b>	Check interval (in minutes)
icap	Checks if the defined ICAP server is available.	If ICAP server is reachable and an Eicar test file and a txt file are handled as expected.		If ICAP server cannot be reached or if the value return is unexpected.		Check the availability of the ICAP or analyze it on the ICAP server.	1440

From:  
<https://help.m-privacy.de/> -

Permanent link:  
<https://help.m-privacy.de/doku.php/en:tightgate-pro:anhang:nagios>

Last update: **2025/03/25 09:50**

